



Sol-Ark Commercial Energy Solutions



A global energy technology leader with over 6 generations of hybrid inverters

Deep engineering expertise in smart energy solutions

A track record of results. For over a decade, Sol-Ark has been solving complex energy challenges with innovation and technology

Powered by a vast ecosystem including thousands of distributors, installers, EPCs, integrators, and battery manufacturers

Trusted by global Fortune 500 companies in telecommunications, retail, big tech, restaurants, and the largest space agency in the world

480V Outdoor and Indoor

Battery Model:

**L3 HV-60kWh
(60K-IP55)**
**L3 HV-60kWh
(60K-IP20)**

System Data		
Compatible Inverter	Sol-Ark 60K-3P-480V-N	
Environmental Rating	Outdoor	Indoor
Cell Chemistry	Lithium Iron Phosphate	
Battery Cabinet Capacity	61.44 kWh	
System Usable Energy ¹	55.30 kWh	
Inverter Grid/Gen/Load Port Rating	200A	
Maximum Input OCPD	200A	
Real Power (backup) Per Inverter	60 kWac	
Max DC-Coupled Solar Per Inverter	78 kWac	
Max AC-Coupled Solar Per Inverter	125 kWac	
Max Battery Cabinets Per Inverter	6	16
Inverter Stacks in Parallel	6 ²	12
Recommend Depth of Discharge	90%	
System Nominal Voltage	614.4V	
System Operating Voltage	499.2V – 700V	
Charge/Discharge Current ³		
• Recommend	50A	
• Nominal/Continuous	100A	
• Peak Discharge (2 mins @ 25°C)	125A	
System Roundtrip Efficiency	90% (25C, 0.5C)	
Product Dimensions (WxDxH)	76x107x226 cm (30x42x89 in)	58x58x162 cm (23x23x64 in)
Net Weight	950 kg (2,095 lbs)	773 kg (1,705lbs)
Mounting Type	Outdoor Enclosure	Freestanding Rack Mount
Operating Temperature ⁴	-30°C – 55°C (-22°F – 131°F)	-20°C – 55°C (-4°F – 131°F)
Humidity	5% – 85%RH	
Operating Altitude ⁵	3000m (9,843 ft)	
Storage Conditions ⁶	-4°F – 95°F Up to 85% RH (non-condensing) State of Charge (SOC) 30%	
Ingress Rating	IP55 (NEMA 3R)	IP20 (NEMA 1)
Noise Level	51 dBA at 30°C (86°F)	< 40 dBA at 30°C (86°F)
Seismic Zone	4	
Communication Port	CAN2.0/RS485	
Battery Module Specifications		
Battery Module Configuration	12s1p	
Battery Module Energy	5.12 kWh	
Battery Module Nominal Voltage	51.2V	
Battery Module Nominal Capacity	100Ah	
Warranty and Certification		
Cycle Life	>6000 Cycles (77°F ± 7°F 0.5C/0.5C, EOL70%)	
Warranty ⁷	10 Years	
Certification	UL1973, UL9540*, UL9540a, UN38.3, FCC, Prop 65	

1. DC usable energy, test conditions: 90% DOD, 0.3C charge and discharge at 25°C. System usable energy may vary due to system configuration parameters.

2. For larger outdoor installations, use the Sol-Ark Mega Ark.

3. The current is affected by temperature and SOC.

4. Charging disconnects below 32°F. Derating occurs above 113°F. Ambient temperature may exceed operating range on IP55 model if using included climate controls. See Sol-Ark technical sales for planning outdoor sites outside of operating temperature range.

5. Battery will operate at a maximum of 1C charge/discharge up to 2000m, above 2000m maximum output is derated to 0.8C, contact Sol-Ark for details.

6. Storage temperature of the battery with no charge or discharge.

7. Battery warranty expires at 6000 cycles or 10-year term, whichever occurs first. 5-year extended warranty option available for inverter only.

8. * Pending